



SECTION

NOTES:

- TUBING UNDER ROADWAY SHALL BE ENCASED IN 2" P.V.C. PIPE SCHEDULE 40 MINIMUM AND EXTEND 4 FEET BEYOND THE EDGES OF PAVEMENT OR BACK OF CURB.
- 2. ANY SERVICE TAPS THAT ARE APPROVED WITHIN PAVEMENT SHALL INCLUDE THE USE OF A 2" CAST IRON GATE VALVE IN LIEU OF THE CORPORATION STOP.

- (2) METER BOX AND PREDRILLED COVER WITH PLUG TO BE LOCATED INSIDE ROW @ PROPERTY LINE (LCU OWNED AND MAINTAINED)
- (3.) POLYETHELENE TUBING, PE 3408, 200 PSI, SDR 9, BLUE (SEE APPROVED MATERIAL LIST)
- 4) STRAIGHT CURB STOP WITH PADLOCK WINGS CONNECTED TO LEE COUNTY WATER METER (SEE APPROVED MATERIAL LIST)
- (5.) $\frac{3}{4}$ " POLYETHELENE, PE 3408, 200 PSI, SDR 9, BLUE (SEE APPROVED MATERIAL LIST) WITH LOCATING WIRE
- 6. 1" POLYETHELENE TUBING, PE 3408, SDR 9, BLUE (SEE APPROVED MATERIALS LIST) WITH LOCATING WIRE
- (7.) MIN. 22 ½" NOT TO EXCEED 45"
- (8) BALL CORPORATION STOP (SEE APPROVED MATERIAL LIST)
- (9.) BRASS "Y" OR "T" CONNECT (SEE APPROVED MATERIAL LIST)
- DOUBLE STRAP SERVICE SADDLE PROVIDE SPRING LOADED TAPPING SADDLE WHEN TAPPING HDPE (SEE APPROVED MATERIAL LIST)
- (11) WATER MAIN
- (12) END OF LCU MAINTENANCE AT METER



NOT TO SCALE